



**Faculty of Manufacturing Engineering**

**PARAMETER OPTIMIZATION ON HYBRID MICRO WIRE  
ELECTRICAL DISCHARGE TURNING**

**Muhammad Akmal bin Mohd Zakaria**

**Master of Science in Manufacturing Engineering**

**2017**

**PARAMETER OPTIMIZATION ON HYBRID MICRO WIRE ELECTRICAL  
DISCHARGE TURNING**

**MUHAMMAD AKMAL BIN MOHD ZAKARIA**

**A thesis submitted  
in fulfillment of the requirements for the degree of Master of Science  
in Manufacturing Engineering**

**Faculty of Manufacturing Engineering**

**UNIVERSITI TEKNIKAL MALAYSIA MELAKA**

**2017**

## DECLARATION

I declare that this thesis entitled “Parameter Optimization on Hybrid Micro Wire Electrical Discharge Turning” is the result of my own research except as cited in the references. The thesis has not been accepted for any degree and is not concurrently submitted in candidature of any other degree.

Signature : .....

Name : MUHAMMAD AKMAL BIN MOHD ZAKARIA

Date : .....

## **APPROVAL**

I hereby declare that I have read this thesis and in my opinion this thesis is sufficient in terms of scope and quality for the award of Master of Science in Manufacturing Engineering.

Signature : .....

Supervisor Name : ASSOC. PROF. DR. RAJA IZAMSHAH  
BIN RAJA ABDULLAH

Date : .....

## **DEDICATION**

This thesis is dedicated to

my beloved and great parents, who never stop giving of themselves in countless ways,  
my beloved brother and sisters, who stands by me when things look bleak and hope this  
thesis may inspire you to excel in any field in which you venture during your life journey

## ABSTRACT

Micro-machining is expected to play an important role in today's manufacturing technology. However, the traditional down-scaling process creates challenges relating to process stability and materials behaviour especially for small difficult-to-machine made materials. Therefore, a suitable material removal process to perform micro-machining on cylindrical components is spark erosion process. In this study, the new hybrid micro-machining process is developed. This process is synonym with the name of wire electrical discharged turning (WEDT) which incorporates a turning process of rotating workpiece to continuous travelling electrode wire in electrical discharged conditions produced by wire electrical discharge machine. The objective of this research is to develop and evaluate the advance machinery and equipment for rotary axis mechanism that is being used to rotate the workpieces. The research focuses on optimizing the process parameter of hybrid WEDT for micro-machining straight shaft cylindrical component made of Ti6Al4V as materials. The issues pertaining to hybrid WEDT process on surface roughness (Ra) in the past have been explored comprehensively. The rotary axis mechanism that works well with WEDM machine has been successfully developed and the micro turning operations has been performed. The parameter optimization consideration on Ra begins with two stage screening. Firstly, the suitable combination parameter and its range is properly selected. Then, the selection of appropriate parameters and range is further screened by Taguchi orthogonal array  $L_{12}$ . From the 11 process parameters that consist of electrical, non-electrical and rotary axis mechanism characteristics, only four has been selected to perform optimization by response surface methodology (RSM) which are intensity of pulse, voltage open, wire tension and rotational spindle speed. The other parameters are fixed at best level to produce low Ra value which is identified by Alicona Infinite Focus microscope (IFM). The optimal Ra that is produced by experiment through desirability approach is as much as  $4.0143 \mu\text{m}$  with relative error as much as 5.9% compared to the prediction. The parameter and its level are pulse intensity of 8 Notch, wire tension of 14.8 Newton, voltage of 7 Notch and rotational spindle speed of 2390 rev/min. The machined parts surface is being deteriorated accordingly to the violent energy density generated by high pulse intensity and voltage, low wire tension and spindle speed.

## ABSTRAK

*Pemesinan mikro dianggarkan memainkan peranan penting dalam teknologi pembuatan kini. Namun, pemesinan penskalaan kecil bagi proses tradisional adalah mencabar, ia berkait dengan kestabilan proses dan sifat bahan terutama jenis bahan sukar dimesin bahkan dalam penskalaan kecil. Oleh itu, proses pemotongan yang sesuai dalam melaksanakan pemesinan mikro pada bendakerja berbentuk silinder adalah proses cucuhan hakisan. Dalam penyelidikan ini, proses pemesinan hibrid mikro terbaru telah dibangunkan. Proses ini sinonim dengan nama pemesinan larik wayar nyahcas elektrik (WEDT) dimana ia menggabungkan putaran bendakerja terhadap wayar elektrod dalam persekitaran nyahcas elektrik yang dibekalkan oleh mesin wayar nyahcas elektrik. Objektif penyelidikan ini untuk membangun dan menilai terhadap mesin dan kelengkapan termaju bagi mekanisme paksi putar yang digunakan untuk memutarakan bendakerja. Penyelidikan ini memfokuskan pengoptimum parameter bagi proses hibrid mikro WEDT dalam pemesinan mikro komponen silinder berbentuk aci lurus yang diperbuat oleh bahan Ti6Al4V. Isu yang berkaitan proses hibrid WEDT terhadap kekasaran permukaan (Ra) pada kajian lepas telah dikaji secara menyeluruh. Mekanisme paksi putaran yang berfungsi dengan baik pada mesin WEDM telah berjaya dibangunkan dan melaksanakan operasi melarik mikro. Pengoptimum parameter untuk Ra bermula dengan dua peringkat penyaringan. Pertama, kombinasi dan julat yang sesuai diantara parameter dipilih. Seterusnya, penyaringan peringkat kedua dilakukan dengan menggunakan teknik Taguchi pada parameter dan julat yang telah dipilih. Daripada 11 parameter yang dipilih, hanya empat sahaja parameter yang dibawa dan dioptimumkan oleh kaedah metodologi permukaan sambutan (RSM) iaitu keamatan denyutan, voltan buka, ketegangan wayar dan kelajuan putaran spindel. Parameter yang lain dikekalkan pada tahap minimum terhadap prestasi Ra yang mana ia diukur oleh mikroskop Alicona Infiniti Fokus Mikroskop (IFM). Keoptimalan Ra hasil daripada eksperimen yang telah dibangunkan dengan kaedah kebolehinginan bernilai  $4.0143 \mu\text{m}$  dengan ralat relatif sebanyak 5.9% apabila dibandingkan dengan nilai ramalan. Kemerostan prestasi pada permukaan bendakerja dialami apabila keamatan denyutan dan voltan buka ditetapkan tinggi disamping ketegangan wayar yang kendur dan kelajuan putaran spindel yang perlahan.*

## ACKNOWLEDGEMENTS

In the name of Allah, the Most Gracious and the Most Merciful.

Alhamdulillah, all praises to Allah the Almighty for His blessing in completing this thesis. Special appreciation goes to my supervisor, Associate Professor Dr. Raja Izamshah bin Raja Abdullah for his supervision and constant support. His invaluable help especially in giving constructive comments and suggestions throughout the experimental and thesis works have contributed to the success of this research. I wish to extend my gratitude to my project supervisor Dr. Mohd Shahir bin Kasim for his inspirational guidance, help and great supervision. I am also thankful to my co-supervisor Dr. Mohd Amran bin Md. Ali. Working with them was indeed a wonderful and learning experience, which I thoroughly enjoyed.

I would like to express my appreciation to the Dean, Faculty of Manufacturing Engineering, Associate Professor Mohd Rizal bin Salleh also to the Deputy Dean, Associate Professor Dr. Hambali bin Arep @ Ariff for their support and help towards my postgraduate affairs.

My acknowledgement also goes to all the assistant laboratory engineer and office staffs of center of advanced manufacturing (AMC) in assisting and sharing their skills, opinions, advices and guidance in handling the equipment throughout the study particularly to Mr. Hanafiah in assisting the fabrication, experimental setup and troubleshoot, Mr. Taufiq in helping to prepare the machines, Madam Aisyah for helping in measurement and Mr. Azhar for assisting in identifying the SEM micrograph.

A big thanks to Research and Innovation Management (CRIM) of Universiti Teknikal Malaysia Melaka for providing MyBrain UTeM assistance for my study and Faculty of Manufacturing for providing experimental facilities used in this project. Special thanks to Ministry of Education Malaysia for the Research Grant Scheme [FRGS/2/2014/TK01/UTEM/03/2].

My deepest gratitude goes to my beloved parents; Mohd Zakaria bin Aziz and Fauziah binti Jaafar and also to my siblings Siti Norhani, Mohd Redzwan and Siti Nurazlinda for their endless love, prayers and encouragement. Also not forgetting my wife, Arbaeyah binti Abdul Razak for her love and care. They are always closest to my joys and sorrows and always there for me. I am also grateful for the support and guidance received from my colleagues. Thank you to all my friends in UTeM for sharing this journey with me.



## TABLE OF CONTENTS

	<b>PAGE</b>
<b>DECLARATION</b>	
<b>APPROVAL</b>	
<b>DEDICATION</b>	
<b>ABSTRACT</b>	<b>i</b>
<b>ABSTRAK</b>	<b>ii</b>
<b>ACKNOWLEDGEMENTS</b>	<b>iii</b>
<b>TABLE OF CONTENTS</b>	<b>iv</b>
<b>LIST OF TABLES</b>	<b>vii</b>
<b>LIST OF FIGURES</b>	<b>ix</b>
<b>LIST OF APPENDICES</b>	<b>xiv</b>
<b>LIST OF SYMBOLS</b>	<b>xv</b>
<b>LIST OF ABBREVIATIONS</b>	<b>xvi</b>
<b>LIST OF PUBLICATIONS</b>	<b>xviii</b>
<b>CHAPTER</b>	
<b>1. INTRODUCTION</b>	<b>1</b>
1.1 Research Background	1
1.2 Problem Statement	4
1.3 Research Objective	6
1.4 Scope of Work	6
1.5 Significance of Studies	7
1.6 Organization of Report	7
<b>2. LITERATURE REVIEW</b>	<b>9</b>
2.1 Introduction	9
2.2 Turning by Wire Electrical Discharge Machining	9
2.3 Rotary Axis Mechanism for Wire Electrical Discharge Machining (WEDM)	13
2.4 Pulse Characteristic between WEDT and WEDM	18
2.5 WEDT Performance Measures: Surface Roughness and Material Removal Rate	21
2.5.1 Surface Roughness	23
2.5.2 Material Removal Rate (MRR)	24
2.5.3 Influences Pulse Characteristics on WEDT Performance Measures	25
2.6 Previous Studies: Influence of WEDT Process Parameters	26
2.6.1 Pulse Off Time	28

2.6.2	Pulse On Time	28
2.6.3	Power	29
2.6.4	Voltage	30
2.6.5	Servo Feed	30
2.6.6	Rotational Spindle Speed	31
2.6.7	Wire Tension	32
2.6.8	Spark Gap	32
2.6.9	Summary of Process Parameters in WEDT	33
2.7	Surface Quality of WEDT Workpieces	33
2.7.1	Macro-Ridges	34
2.8	Titanium Alloy	34
2.8.1	Challenges in Machining of Titanium Alloy	36
2.9	Design of Experiment (DOE)	37
2.9.1	Taguchi Orthogonal Arrays (OAs)	39
2.9.1.1	S/N Ratio	41
2.9.1.2	Analysis of Variance (ANOVA)	43
2.9.2	Response Surface Methodology	44
2.9.2.1	Central Composite Design (CCD)	46
2.9.2.2	Application of RSM in Process Optimisation and Modelling	48
2.9.2.3	Optimization using Desirability Function	49
2.10	Concluding Remarks	51
<b>3.</b>	<b>MATERIALS AND METHODS</b>	<b>53</b>
3.1	Introduction	53
3.2	Design and Construction of Rotary Axis Mechanism	58
3.2.1	Rotary Spindle and Housing	59
3.2.2	Base Frame and Motor Bracket	63
3.2.2.1	Design Base Frame and Motor Bracket	63
3.2.3	Speed Controller	65
3.2.3.1	Design and Develop of Speed Controller	65
3.2.3.2	Program PIC Microcontroller	68
3.2.4	Final Assembly	69
3.3	Hybrid Micro WEDT Experimental	73
3.3.1	Research Material: Ti6Al4V	73
3.3.2	Electrode Material: Brass	75
3.3.3	Wire EDM Machine	76
3.3.3.1	Parameter	77
3.3.3.2	Pulse Waveforms Characteristics	79
3.3.4	Experimental Setup	80
3.3.5	Machining Strategies	83
3.3.6	Performance Criteria Evaluation Method	84
3.3.6.1	Arithmetic Average Surface Roughness (Ra)	84
3.3.6.2	Weight Differences	87
3.3.6.3	Surface Morphologies	87
3.4	Selection of Process Parameter (Screening)	88

3.4.1	Method in Selection Range of Parameter for Machining Capability	88
3.4.2	Taguchi Design Scheme (Orthogonal Array L <sub>12</sub> )	92
3.5	Machining with Highly Influences WEDT Process Parameters	95
3.5.1	RSM: Face-centred Central Composite Design Scheme	96
3.5.2	Validation of the Process Model	98
3.6	Summary	99
<b>4.</b>	<b>RESULTS AND DISCUSSIONS</b>	<b>100</b>
4.1	Introduction	100
4.2	Evaluation of the rotary axis mechanism	101
4.3	Experimental Screening Results	104
4.3.1	Selection of Process Parameter: Machining Capability	104
4.3.2	Taguchi Orthogonal Array on Surface Roughness	106
4.3.3	Summary of Screening Analysis	115
4.3.4	Scientific Finding	117
4.3.4.1	Stabilizer E	117
4.3.4.2	Spindle Direction	119
4.4	Parameter Optimisation by Employing Face-centred Central Composite Design (FCCD)	124
4.4.1	Assessing Process Parameters by using Statistical Analysis	124
4.4.2	Comparative and Determination of Significant Terms on Surface Roughness	130
4.4.3	Model Validation	139
4.4.4	Parameter Optimization	141
4.4.5	Surface Topography of Hybrid Micro WEDT Surface	145
4.4.5.1	Interaction between Intensity of Pulse and Wire Tension	145
4.4.5.2	Interaction between Voltage and Wire Tension	147
4.4.5.3	Interaction between Rotational Spindle Speed and Wire Tension	148
4.5	Summary	150
<b>5.</b>	<b>CONCLUSIONS AND RECOMMENDATIONS</b>	<b>151</b>
5.1	Conclusion	151
5.2	Recommendations for Future Work	154
	<b>REFERENCES</b>	<b>157</b>
	<b>APPENDICES</b>	<b>168</b>

## LIST OF TABLES

TABLE	TITLE	PAGE
2.1	The summarization of the previous studies in WEDT in dealing with materials type and the value of each performance measure	22
2.2	WEDT process parameters in existing literatures	27
2.3	The challenges in machining Ti6Al4V by conventional machining	36
2.4	The polynomial equation model in RSM	45
3.1	Name, dimension, specification details and material of the component	61
3.2	Components and their functions in rotary axis mechanism	61
3.3	Electronic component and their descriptions (Cytron Technologies, 2011)	67
3.4	The specifications of Ti6Al4V (E Steel SDN. BHD., n.d.)	74
3.5	The ultrasonic bath parameter during specimens cleaning preparation	74
3.6	Wire electrodes properties (EDM Tools, n.d.)	75
3.7	Mitsubishi RA90 parameters and their descriptions (Mitsubishi-Electric-Corporation, n.d.)	78
3.8	The details procedure of installing the workpiece, zero-positioning electrode wire and the approach of control radial depth of cut	82
3.9	Design of experiment strategies comparison	89
3.10	Parameter conditions for Tungsten Carbide (Mitsubishi-Electric-Corporation, n.d.)	91
3.11	$L_{12}$ orthogonal array for eleven factors and two levels ( $2^{11}$ )	94
3.12	11 assigned design variables, units, notations and levels for Taguchi OA $L_{12}$	95
3.13	Face-centred central composite design (FCCD) used in this research study for $k=4$	98

4.1	Rotary axis mechanism fabrication capabilities of shape and design	103
4.2	The well combination among the parameters	105
4.3	Summary of the example machining trials	106
4.4	Experimental results	108
4.5	Percentage contribution of S/N ratio for Ra	110
4.6	Response table for Signal to Noise Ratios	111
4.7	S/N ratio ANOVA for Ra	112
4.8	Selection of the parameters for RSM based on rank	116
4.9	Selected fixed and vary parameters with respective to best level and range for RSM	116
4.10	Surface roughness result	125
4.11	Sequential model sum of squares analysis for surface roughness model	127
4.12	Lack of fit test for surface roughness model	127
4.13	Model summary statistics for surface roughness model	127
4.14	ANOVA for response of surface roughness	128
4.15	R-squared analysis for response surface quadratic model of surface roughness	128
4.16	Result for confirmation experiments for estimated responses	140
4.17	The approach of optimization to suit the Mitsubishi RA90 machine capability	143
4.18	Optimal combination of input factors for single response optimization	143

## LIST OF FIGURES

FIGURE	TITLE	PAGE
1.1	Miniaturized components in medical, metrology and defense applications (Janson et al. 1999; Sheu, 2004; Jee and Kim, 2011; Rees, 2011; Zhu et al. 2016)	2
1.2	Workpiece deflection in micro turning (Rahman, 2004)	4
2.1	Wire electrical discharge turning (WEDT) principle	12
2.2	Wire electrical discharge grinding (WEDG) a) Twin wire guided (Lim et al. 2003) b) Single wire guided (Chern and Wang, 2007)	12
2.3	The phenomena of discharge area in WEDT along the electrode wire	13
2.4	Rotary axis mechanism develop by Qu et al. (2002a)	14
2.5	Rotary axis mechanism developed by Haddad and Tehrani (2008)	14
2.6	Rotary axis mechanism developed by Mohammadi et al. (2008)	15
2.7	Cross-section view rotary axis mechanism developed by Janardhan and Samuel (2010)	16
2.8	Rear view of rotary axis mechanism developed by Janardhan and Samuel (2010)	16
2.9	Rotary axis mechanism developed by Rajkumar et al. (2012)	17
2.10	Rotary axis mechanism developed by Parthiban et al. (2013)	17
2.11	Discrimination between arc, short and normal pulses in WEDM process (Liao and Woo, 1997)	19
2.12	Pulse trains for WEDT (Janardhan and Samuel, 2010)	21
2.13	Pulse trains for WEDM (Janardhan and Samuel, 2010)	21
2.14	Coordinates used for surface roughness measurement defined by Ra equation (Kalpakjian and Schmid, 2006)	24
2.15	Process parameters and performance measures of WEDT process	26

2.16	SEM micrographs of macro-ridges and ideal arcs on WEDT workpieces machined surface (Haddad et al. 2010)	34
2.17	Microvascular anastomosis micro ring-pin system (Jee and Kim, 2011)	35
2.18	Region of interest versus region of operability (Anderson, 2016)	39
2.19	Central composite design for three factors (Voyer, 2003)	47
2.20	Face-centred central composite design (FCCD) for three factors (Voyer, 2003)	48
2.21	The scenarios for the response (y) (a) ‘the larger the better’, (b) ‘the smaller the better’, (c) ‘the target is the best’ (Myers et al. 2009)	51
3.1	Flowchart of the research methodology	55
3.2	Prototype architecture of the rotary axis mechanism	58
3.3	Pre-assembly rotary spindle and housing (a) Front side (b) Back side	59
3.4	Radial oil seal and ceramic bearing placed in the housing	60
3.5	The fabricated rotary axis mechanism base frame	64
3.6	Completed DC motor with set of motor mount heatsink and its insulator	65
3.7	The speed controller integration of SK40C, MD10C, voltage regulator and DC motor	67
3.8	The example of the coding that is used in this research study	69
3.9	UIC00B Programmer	69
3.10	CAD design of final assembly of rotary axis mechanism for hybrid micro WEDT	71
3.11	The actual final assembly of rotary axis mechanism for hybrid micro WEDT	72
3.12	The actual final assembly of rotary axis mechanism for hybrid micro WEDT	72
3.13	The final assembly of speed controller	73
3.14	Rear side of speed controller	73
3.15	The specimens is being immersed and cleaned by ultrasonic bath method	75
3.16	0.25 mm of brass electrode wire that is being used in this research work	76
3.17	Mitsubishi brand of the WEDM machine specific model RA90	77

3.18	Mitsubishi RA90 pulse characteristics (Mitsubishi-Electric-Corporation, n.d.)	80
3.19	The position of rotary axis mechanism on WEDM machine table	81
3.20	The details configuration of rotary axis mechanism to the WEDM machine including clamped workpiece and position of electrode wire	81
3.21	Straight turning program with single pass path condition	84
3.22	Alicona Infinite Focus Microscope (IFM)	85
3.23	An optical image of machined surface of micro-cylindrical part by hybrid WEDT	86
3.24	The software Infinite Focus interface to measure the arithmetic average surface roughness	86
3.25	Mettler Toledo analytical balances	87
3.26	Scanning Electron Microscope (Model EVO 50 United Kingdom)	88
3.27	The comparison between full factorial and fractional factorial in design of experiment strategies	90
3.28	The type of machine error if encountered a) Wire breakage b) Insufficient sparked energy	90
3.29	The parameter screening process flowchart	93
3.30	Face-centred Central Composite Design (Whitcomb and Anderson, 2004)	96
4.1	Rotation of spindle is measured by laser type Tachometer	102
4.2	Results of the repeatable dynamic run-out of the spindle with varying rotational spindle speeds	102
4.3	Summarization of hybrid micro WEDT operating conditions percentage contribution to the Ra by employing Taguchi Orthogonal Array L12	110
4.4	Main effects plot for S/N ratios of Ra results	113
4.5	Comparison of pulse trains a) WEDM and b) Hybrid Micro WEDT	119
4.6	Movement of fragments while encountering dissimilar force direction for upward spindle direction	121
4.7	Movement of fragments while encountering similar force direction for downward spindle direction	121
4.8	The progression of the fragments removal by ultrasonic	123



4.9	Model validation plot for Normal % probability of internally studentized residuals	129
4.10	Model validation plot for relationship between the observed and the predicted	130
4.11	Perturbation plot for surface roughness performance	131
4.12	The occurrence of macro-ridges in hybrid micro WEDT workpiece machined surface	133
4.13	Response surface showing the interactive effect of intensity of pulse and wire tension on surface roughness at rotational spindle speed = 1400 rev/min and voltage = 7 Notch	134
4.14	Response surface showing the interactive effect of wire tension and voltage on surface roughness at rotational spindle speed = 1400 rev/min and intensity of pulse = 9 Notch	136
4.15	Response surface showing the interactive effect of rotational spindle speed and wire tension on surface roughness at intensity of pulse = 9 Notch and voltage = 7 Notch	138
4.16	Comparison of predicted to the actual validation for surface roughness (Ra)	141
4.17	Numerical optimization report on solutions by Design-Expert software	142
4.18	Optimal surface roughness plot generated by Alicona software Infinite Focus	144
4.19	Perturbation plot of optimization for surface roughness at intensity of pulse = 8 Notch, voltage = 7 Notch, wire tension = 14.80 Newton and rotational spindle speed = 2390 rev/min with prediction result arithmetic average surface roughness = 4.26684 $\mu\text{m}$	144
4.20	Ramps report on numerical optimization for optimum surface roughness by Design-Expert software	145
4.21	a) IFM micrograph b) SEM micrograph of hybrid micro WEDT machined surface (under Ra: 4.531: pulse intensity=10, voltage=6, wire tension=12.2, rotational spindle speed=400) experiment number 2	146
4.22	a) IFM micrograph b) SEM micrograph of hybrid micro WEDT machined surface (under Ra: 4.420: pulse intensity=8, voltage=6, wire tension=14.8, rotational spindle speed=400) experiment number 3	147
4.23	a) IFM micrograph b) SEM micrograph of hybrid micro WEDT machined surface (under Ra: 4.634: pulse intensity=8, voltage=8, wire tension=12.2, rotational spindle speed=400) experiment number 9	148

4.24	a) IFM micrograph b) SEM micrograph of hybrid micro WEDT machined surface (under Ra: 4.420: pulse intensity=8, voltage=6, wire tension=14.8, rotational spindle speed=400) experiment number 3	148
4.25	a) IFM micrograph b) SEM micrograph of hybrid micro WEDT machined surface (under Ra: 4.672: pulse intensity=10, voltage=8, wire tension=12.2, rotational spindle speed=400) experiment number 10	149
4.26	a) IFM micrograph b) SEM micrograph of hybrid micro WEDT machined surface (under Ra: 4.493: pulse intensity=10, voltage=8, wire tension=14.8, rotational spindle speed=2400) experiment number 16	149

## LIST OF APPENDICES

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
A	Rotary Axis Mechanism Drawing and Parts	168
B	Speed Controller Coding	170
C	Geometrical Features of WEDT Micro-machining	174
D	Datasheet of Titanium Ti6Al4V	177
E	Approach for Optimization	179

## LIST OF SYMBOLS

$\sigma$	-	(Sigma) units for stress calculation
$\mu$	-	(Micro) metric unit denoting a factor of $10^{-6}$ or represent small
$\alpha$	-	(Alpha) coded-unit distance for axial points in central composite design
$\delta$	-	Deflection
df	-	Degrees of Freedom
k	-	number of factors in design
$R^2$	-	Index of determination
n	-	number of observations in sample
P	-	Probability Value
V	-	(volt) unit for electric potential difference
D	-	Diameter
T	-	Thickness
ID	-	Inside Diameter
OD	-	Outside Diameter
Pa	-	(pascal) unit of pressure/stress
$\Omega$	-	(Ohm) unit of electrical resistance
LA	-	Machine power supply low
MP	-	Machine power supply medium
HP	-	Machine power supply high
L, l	-	Length
Ra	-	Arithmetic average surface roughness

## LIST OF ABBREVIATIONS

3D	-	Three Dimension
ABEC	-	Annular Bearing Engineering Committee
AC	-	Alternating Current
AISI	-	American Iron and Steel Institute
ANOVA	-	Analysis of Variance
C.V.	-	Coefficient of Variation
CAD	-	Computer-Aided Design
CAM	-	Computer-Aided Manufacturing
CCD	-	Central Composite Design
CNC	-	Computer Numerical Control
CWEDT	-	Cylindrical Wire Electrical Discharge Turning
DC	-	Direct Current
EDM	-	Electrical Discharge Machining
FCCD	-	Face-centred Central Composite Design
FI	-	Factor Interaction
HSS	-	High Speed Steel
ICSP	-	In Circuit Serial Programming
IDE	-	Integrated Development Environment
IFM	-	Infinite Focus Microscope
$I_p$	-	Intensity of Pulse
ISO	-	International Standardization Organization
LCD	-	Liquid-Crystal Display
LED	-	Light-Emitting Diode
LQ	-	Liquid Quantity
LR	-	Liquid Resistivity

M	-	Metric
MRR	-	Material Removal Rate
OA	-	Orthogonal Array
OFF	-	Off Time
PIC	-	Programmable Interface Controllers
PRESS	-	Predicted Residual Error Sum of Squares
PT	-	Pre-Tension
PWM	-	Pulse-Width Modulation
RSM	-	Response Surface Methodology
SA	-	Stabilizer A
SB	-	Stabilizer B
SC	-	Stabilizer C
SE	-	Stabilizer E
SEM	-	Scanning Electron Microscopy
Si <sub>3</sub> N <sub>4</sub>	-	Silicon Nitride
Ti6Al4V	-	Titanium Alloy Grade 5
USB	-	Universal Serial Bus
VG	-	Voltage Gap
V <sub>o</sub>	-	Voltage Open
WEDG	-	Wire Electrical Discharge Grinding
WEDM	-	Wire Electrical Discharge Machining
WEDT	-	Wire Electrical Discharge Turning
WS	-	Wire Speed
WT	-	Wire Tension

## LIST OF PUBLICATIONS

### Journals:

1. Izamshah, R., Akmal, M., Kasim, M.S., Sundi, S.A. and Hadzley, M., 2016. A Statistical Comparison in Selection of Wire-EDM Process Parameters for Machining Titanium Alloy. *Journal of Advanced Manufacturing Technology (JAMT)*, 10(2), pp. 45-56.
2. Izamshah, R., Akmal, M. and Kasim, M.S., 2017. Improvement of the Wire Compensation Configuration Model for Improving Part Accuracy in Cylindrical Wire Electrical Discharge Turning. *International Journal of Manufacturing Technology and Management*. (In Press)(Scopus)
3. Izamshah, R., Akmal, M., Kasim, M.S., and Amran, M., 2017. Emerging Hybrid Wire Electro Discharge Turning for Micro Parts Fabrication in the Defence Technological Area: A Feasibility Study. *Journal of Fundamental and Applied Sciences*, 9(3S), pp.176-188. (ISI)
4. Izamshah, R., Akmal, M., Amran, M., and Kasim, M.S., 2017. Parametric Study on Parameter Effects in Hybrid Micro Wire Electrical Discharge Turning. *Journal of Advanced Manufacturing Technology (JAMT)*. (Accepted)(Scopus)
5. Izamshah, R., Akmal, M., Amran, M., and Kasim, M.S., 2017. Performance Evaluation of Rotary Mechanism Characteristics by Response Surface Methodology in Cylindrical Wire Electrical Discharge Turning. *Advances in Materials and Processing Technologies*. (Accepted)

### Proceedings:

1. Akmal, M., Izamshah, R., Kasim, M.S., Hadzley, M., Amran, M. and Ramli, A., 2016. Configuration of Wire Positioning To Minimize Parts Error in Wire Electrical Discharge Turning (WEDT), *Proceedings of International Conference on Advanced Processes and Systems in Manufacturing (APSIM 2016)*, Kuala Lumpur, Malaysia, 28-30 August 2016. National University of Malaysia Publisher. (ISI)
2. Akmal, M., Izamshah, R., Kasim, M.S., Hadzley, M., Amran, M. and Ramli, A., 2016. Development of a Rotary Axis Mechanism for Wire EDM Turning

(WEDT). *Proceedings of Mechanical Engineering Research Day 2016 (MERD'16)*, Melaka, Malaysia, 31 March 2016. Universiti Teknikal Malaysia Melaka Publisher. (ISI)

3. Izamshah, R., Akmal, M., Kasim, M.S., Amran, M., Ramli, A. and Liew, P.J., 2016. Emerging Hybrid Wire EDM Turning (HWEDT) In Defence Technological Area for Micro Parts Fabrication: A Feasibility Study, *Proceedings of the Asia Pacific Conference on Defence & Security Technology (DSTC 2016)*. Putrajaya, Malaysia, 15-17 August 2016. National Defence University of Malaysia Publisher.
4. Akmal, M., Izamshah, R., Kasim, M.S., Hadzley, M., Amran, M. and Ramli, A., 2016. Performance Evaluation of Rotary Mechanism Characteristics by Response Surface Methodology in Cylindrical Wire Electrical Discharge Turning. *Proceedings of Advances in Materials and Processing Technologies (AMPT 2016)*. Kuala Lumpur, Malaysia, 8-11 November 2016. University of Malaya Publisher.