



**IMPROVING THE EFFICIENCY AND RELIABILITY OF CONE
LAYING AND COLLECTING (C2L) MACHINE USING TRIZ
METHOD**



MASTER OF SCIENCE IN MECHANICAL ENGINEERING

2024



Faculty of Mechanical Technology and Engineering

**IMPROVING THE EFFICIENCY AND RELIABILITY OF CONE
LAYING AND COLLECTING (C2L) MACHINE USING TRIZ
METHOD**

Muhammad Reza bin Zainal Abidin
اونيور سيتي تیکنیکل ملیسیا ملاک
UNIVERSITI TEKNIKAL MALAYSIA MELAKA


Master of Science in Mechanical Engineering

2024

**IMPROVING THE EFFICIENCY AND RELIABILITY OF CONE LAYING AND
COLLECTING (C2L) MACHINE USING TRIZ METHOD**

MUHAMMAD REZA BIN ZAINAL ABIDIN

**A thesis submitted
in fulfillment of the requirements for the degree of
Master of Science in Mechanical Engineering**



UNIVERSITI TEKNIKAL MALAYSIA MELAKA

2024

DEDICATION

This thesis is wholeheartedly dedicated to my wife, Aisyatul Badriah binti Abdul Ghani for her endless support and confidence in my journey, for believing in me at every turn. Her patience, understanding, and countless sacrifices made this achievement possible. I also dedicate this thesis to my children, Nur Iman Raihanah and Hamzah Aziz, who are my constant source of inspiration and joy. I hope that my journey inspires you to dream big and always work hard towards your dreams.



ABSTRACT

PLUS Berhad (PLUS) executes the temporary signing procedure when maintenance or repair works needs to be done along the highway. Setting up cones around the work area would inform incoming traffic of the lane closure, thus helping the drivers to steer into open lanes. Manually handling the cones impacts the health of the workers while also exposes the workers to the potential of being hit by live traffic and other safety hazards as well. The Cone Laying and Collecting (C2L) semi-automated machine was then developed to address the health and safety issues faced by the workers. The machine's features enable it to lay and collect cones as per PLUS requirements. However, the machine has not yet been tested on its reliability and operational efficiency when under actual working condition, which is a crucial requirement for it to replace the manual cone handling procedure. In this thesis, the C2L machine was tested under several parameters. During the laboratory test, the C2L machine was tested on a test rig to determine the impact of road surface condition on the machine's operation. The operational efficiency of the machine and the mechanical failures that occurred during the test were analysed. TRIZ methodologies were then used on redesigning the machine to address the mechanical failures and further improve the machine's efficiency and reliability. The improved C2L machine was then tested under the field test to determine if it can lay and collect cones according to PLUS requirement. The result from the Laboratory Test showed that the operational efficiency of the C2L machine was consistent on both smooth (Test Motion A) and uneven surface (Test Motion B), suggesting that the efficiency of the C2L machine is not impacted by the road condition. For Test Motion A, the mean of the Total distance traveled on the test rig per minute was 9.43 (m/min), while the median was 9.81 (m/min). For Test Motion B, the mean was 9.54 (m/min), and the median was 10.34 (m/min). Next, the mean of the Total actual distance travelled per minute under Test Motion A was 77.25 (m/min) while the median was 81.63 (m/min). The mean under Test Motion B was 76.17 (m/min) while the median was 82.59 (m/min). The third operational data that was analysed was the Total laying and collecting movements per minute. For Test Motion A, the mean was 7.73 (count/min) while the median was 8.13 (count/min). For Test Motion B, the mean was 7.62 (count/min) while the median was 8.26 (count/min). In terms of reliability analysis, three failed components were redesigned using TRIZ methodologies. The welded joint had a high MTTR (1:00:00), as did the hook spring (1:50:00), while the PLC had low MTTF (0:10:12) and MTBF (0:12:16). These results indicate that these three components may severely affect the reliability of the C2L machine. The redesigned C2L 02 machine was then tested under several Field Test parameters. Overall, the results showed that the machine could lay and collect cones as per PLUS requirements. The time to lay and collect 10 sets of safety cones and 10 sets of super cones during Field Test 1 was consistently 5 minutes across two days. For Field Test 2, the time lay and collect 20 sets of cones in a straight and tapered orientation remained at 10 minutes on both days. These positive results suggested that the C2L 02 machine is reliable and operationally efficient to execute the cone laying and cone collecting activities along PLUS highway. It enhances safety and efficiency in highway maintenance by reducing worker risks and physical strain, leading to fewer injuries and better operational continuity.

PENINGKATAN KECEKAPAN DAN KEBOLEHPERCAYAAN MESIN CONE LAYING AND COLLECTING (C2L) MENGGUNAKAN KAEDAH TRIZ

ABSTRAK

PLUS Berhad (PLUS) melaksanakan prosedur penutupan jalan setiap kali kerja penyelenggaraan dilakukan di sepanjang lebuh raya. Kon di lokasi kerja bertindak sebagai amaran awal untuk memberitahu pengguna tentang penutupan lorong agar pemandu dapat beralih ke lorong yang terbuka. Pengendalian kon secara manual ini didapati memberi kesan buruk kepada kesihatan pekerja, mendedahkan pekerja kepada potensi dilanggar oleh kenderaan dan risiko keselamatan lain. Mesin “Cone Collecting and Laying” (C2L) telah dibangunkan untuk mengatasi isu-isu ini. Walaupun ciri-ciri mesin ini membolehkannya meletak dan mengangkat kon, namun mesin ini belum diuji dari segi kebolehpercayaan dan kecekapan operasinya di bawah kondisi kerja sebenar, yang merupakan keperluan penting untuk mesin ini dibolehkan untuk mengganti prosedur pengendalian kon secara manual. Dalam tesis ini, mesin C2L telah diuji pada rig ujian untuk menentukan kesan keadaan permukaan jalan terhadap operasi mesin. Kecekapan operasi mesin kemudian dianalisis menggunakan analisis deskriptif. Kegagalan mekanikal dan komponen yang berlaku semasa ujian juga dianalisis. Mesin C2L yang baru tersebut kemudian diuji di bawah ujian lapangan. Ujian ini akan menentukan jika mesin C2L yang telah diperbaharui dapat melaksanakan prosedur meletak dan mengangkat kon di sepanjang jalan lurus dan rata mengikut keperluan PLUS. Hasil dari ujian makmal menunjukkan bahawa kecekapan operasi mesin C2L adalah konsisten apabila diuji di atas permukaan yang licin dan permukaan tidak rata, yang menunjukkan bahawa kecekapan mesin itu tidak dipengaruhi oleh keadaan jalan. Berdasarkan analisis kebolehpercayaan, tiga komponen yang gagal ketika ujian makmal telah direka semula menggunakan metodologi TRIZ, bagi meningkatkan kebolehpercayaan mesin C2L. Apabila mesin C2L 02, iaitu mesin yang telah diperbaharui, diuji di bawah parameter ujian lapangan, mesin tersebut telah menunjukkan yang ianya berupaya untuk meletak dan mengangkat kon tanpa gagal. Hasil positif ini menunjukkan bahawa mesin ini berpotensi melaksanakan aktiviti meletak dan mengumpul kon di sepanjang lebuh raya PLUS dan menggantikan prosedur manual yang sedia ada. Penggunaan mesin ini berpotensi untuk meningkatkan keselamatan dan kecekapan dalam penyelenggaraan lebuh raya. Ia secara signifikan mengurangkan risiko keselamatan pekerja dan tekanan fizikal dalam pengendalian kon, disamping mengurangkan kes kecederaan berkaitan kerja, sekaligus meningkatkan imej PLUS sebagai organisasi yang memberi fokus kepada keselamatan. Penggunaan C2L juga akan membuka jalan untuk kajian inovatif baru dijalankan oleh PLUS. Dari segi akademik, proses pembangunan mesin C2L menawarkan templat komprehensif untuk penyelidikan teknologi baru. Model penyelidikan ini meliputi kajian terhadap keselamatan dan reka bentuk kejuruteraan kebolehpercayaan operasi. Penyelidikan ini boleh menjadi panduan untuk kajian yang bertujuan untuk menukar sesuatu proses manual ke sistem separa automatik dengan menawarkan panduan untuk menangani masalah kompleks dari pelbagai aspek.

ACKNOWLEDGEMENT

In the Name of Allah, the Most Gracious, the Most Merciful. First and foremost, I would like to take this opportunity to express my sincere gratitude to my supervisors, Assoc. Prof. Ir. Ts. Dr. Mohd Azli bin Salim and Assoc. Prof. Dr. Nor Azmmi bin Masripan. Their expertise and continuous guidance were instrumental in shaping this thesis. Also, their confidence in my own ability to execute and complete this research had fuelled my motivation to complete my studies. I am also grateful to Ts. Dr. Norbazlan bin Mohd. Yusof, the Head of Unit of Innovation and Centre of Excellence Department, PLUS Berhad for providing insights on the highway maintenance procedures which strengthen this research. Finally, I would like to express my appreciation to PLUS Berhad for providing access to their internal resources and operational data which became the foundation for this work.





TABLE OF CONTENTS

	PAGES
DECLARATION	
APPROVAL	
DEDICATION	
ABSTRACT	i
ABSTRAK	ii
ACKNOWLEDGEMENT	iii
TABLE OF CONTENTS	iv
LIST OF TABLES	vii
LIST OF FIGURES	ix
LIST OF ABBREVIATIONS	xiv
LIST OF SYMBOLS	xvi
LIST OF APPENDICES	xvii
LIST OF PUBLICATIONS	xviii
CHAPTER	
1. INTRODUCTION	1
1.1 Background	1
1.2 Problem Statement	7
1.3 Research Objective	8
1.4 Scope of Research	8
1.5 Thesis Outline	10
2. LITERATURE REVIEW	12
2.1 Introduction	12
2.2 PLUS Malaysia Berhad	14
2.2.1 Temporary Signing Procedure Along PLUS Highway	16
2.2.2 Safety Issues Related to the Manual procedure of Laying and Collecting Cones During Temporary Signing Procedure	20
2.3 Existing Technologies on Cone Collecting and Laying Procedure	33
2.3.1 Auto Cone by Verdegro Group	34
2.3.2 X-Cone 2.0 by Janschitz GmbH	35
2.3.3 Dynamic Lift System (DLS) by J-Tech	38
2.3.4 Adaptability and Safety Issues on Existing Cone Laying and Collecting Activities	42
2.4 The Cone Collecting and Laying (C2L) Machine	43
2.4.1 The Test Bed – Holds C2L to the Lorry During Operation	44
2.4.2 The C2L Body – Main Component of C2L Machine	45
2.4.3 Guide Post – Setting the Cones for Operation	55
2.4.4 Operating the C2L Machine	57
2.4.5 Improving the Safety of Cone Collecting and Laying Procedure Using C2L Machine	64
2.5 Determining the Readiness of the C2L Machine to be Used Under Actual Working Condition	66
2.5.1 The Importance of Laboratory Test on C2L Machine	67

2.5.2	The Importance of Reliability Test on C2L Machine	69
2.5.3	The Importance of Field Test on C2L Machine	74
2.6	TRIZ Methodologies for Innovation	75
2.6.1	Fundamental Concepts of TRIZ	77
2.6.2	Methodologies of TRIZ	79
2.6.3	Application of TRIZ Methodologies for Innovation	83
2.6.4	Application of TRIZ Methodologies in Improving System Reliability	88
2.7	Summary	91
3.	METHODOLOGY	93
3.1	Introduction	93
3.1.1	The Cone Laying and Collecting (C2L) Machine Used in Highway Operation	96
3.2	Research Design	97
3.3	The Methodology	99
3.4	Laboratory Test	101
3.4.1	Test Rig System Mechanism	103
3.4.2	The Procedure for Laboratory Test	108
3.4.3	The Parameters Involved in Laboratory Test	110
3.4.4	Data Collection	111
3.5	Reliability Analysis	114
3.5.1	Static Analysis	115
3.5.2	Dynamic Analysis	117
3.5.3	Determining the Reliability Metrics from Machine Failure Data	123
3.6	Analysing the Failure Data and Ideating Innovative Solution	124
3.6.1	Function Model (FM)	125
3.6.2	Substance-Field (Su-Field) Analysis	128
3.6.3	The 76 Standard Inventive Solution	134
3.6.4	Redesigning the C2L Machine	134
3.7	Field Test	135
3.7.1	C2L 02 Set-up	136
3.7.2	C2L 02 Field Test Procedure	137
3.7.3	C2L 02 Field Test Parameter	139
3.7.4	Analysing the Data from the Field Test	140
3.8	Summary	141
4.	RESULT AND DISCUSSION	142
4.1	Introduction	142
4.2	Analysis of Laboratory Test	143
4.2.1	Test Motion A	144
4.2.2	Test Motion B	152
4.2.3	Analyzing the Operational Data from Test Motion A and Test Motion B	157
4.3	Result and Analysis on Reliability Analysis	172
4.3.1	Reliability Metrics Analysis from Test Motion A	172
4.3.2	Reliability Metrics Analysis from Test Motion B	176

4.3.3	Discussion from Reliability Metrics	179
4.4	Improving the Design of C2L Machine Using TRIZ Methodologies	181
4.4.1	Analysing the C2L Machine Failure from Test Motion A and Test Motion B	181
4.4.2	Improving the Machine Design Using TRIZ Methodologies	184
4.4.3	New C2L Design Called C2L 02	193
4.5	Analysis of Field Test for C2L 02	195
4.5.1	Field Test Operational Data	196
4.5.2	Analyzing the Operational Data of Field Test	200
4.5.3	Summary of the Field Test	201
4.6	Summary	203
5.	CONCLUSION AND RECOMMENDATIONS FOR FUTURE RESEARCH	205
5.1	Introduction	205
5.2	Summary of the Research Objectives	206
5.3	Research Contributions	207
5.4	Practical Implications and Beneficiaries	217
5.5	Limitations of The Present Study	219
5.6	Future Works	221
5.7	Summary	222
	REFERENCES	224
	APPENDICES	238



اونيورسيتي تيكنيكل مليسيا ملاك
UNIVERSITI TEKNIKAL MALAYSIA MELAKA

LIST OF TABLES

TABLE	TITLE	PAGE
Table 2.1	Breakdown of highways maintained by PLUS Malaysia Berhad	16
Table 2.2	Comparison of Commercial Systems' Compliance with PLUS Requirements for Cone Laying and Collecting Operation	41
Table 3.1	Summary of Operational Data	113
Table 3.2	Summary of failures during Test Motion A and Test Motion B	114
Table 3.3	Components analysed to determine the reliability metrics	124
Table 3.4	The Grouping of 5 Classes of the 76 Standard Inventive Solutions	134
Table 3.5	Summary of Operational Data from Field Test	140
Table 4.1	Summary of Operational Data from Test Motion A	144
Table 4.2	Observation of the condition of the C2L machine and test rig during Test Motion A	146
Table 4.3	Summary of Operational Data from Test Motion B	152
Table 4.4	Observation of the condition of the C2L machine and test rig during Test Motion B	153
Table 4.5	Summary of Total distance travelled on test rig per minute (m/min) between Test Motion A and Test Motion B	158
Table 4.6	Descriptive Analysis between Test Motion A and Test Motion B on the Total distance travelled on test rig per minute (m/min)	160
Table 4.7	Summary of Total actual distance travelled per minute (m/min) between Test Motion A and Test Motion B	164
Table 4.8	Descriptive Analysis between Test Motion A and Test Motion B on the total actual distance travelled per minute (m/min)	165
Table 4.9	Summary of Total laying and collecting movements per minute (count/min) between Test Motion A and Test Motion B	167
Table 4.10	Descriptive Analysis between Test Motion A and Test Motion B on the Total laying and collecting movements per minute (count/min)	168

TABLE	TITLE	PAGE
Table 4.11	Data from C2L machine failures during Test Motion A	172
Table 4.12	Reliability Metrics of failed components during Test Motion A	175
Table 4.13	Data from C2L machine failures during Test Motion B	176
Table 4.14	Reliability Metrics of failed components during Test Motion B	178
Table 4.15	Summary of Reliability metrics of failed components	180
Table 4.16	Summary of failures during Test Motion A and Test Motion B	182
Table 4.17	Operation Data from Field Test	197



LIST OF FIGURES

FIGURE	TITLE	PAGE
Figure 2.1	Infographic of the expressway maintained by PLUS Malaysia Berhad	15
Figure 2.2	Different sections within the Traffic Control Zone	18
Figure 2.3	Cone spacing according to zones during the temporary signing procedure	19
Figure 2.4	The worker at the back of the lorry will pass a cone to the worker on the pavement who will then arrange it accordingly	21
Figure 2.5	Transferring the cones from pavement to the back of the lorry involves lifting heavy cones while twisting the torso	22
Figure 2.6	The manual procedure of laying and collecting cones for temporary signing procedure exposes the workers to live traffic	24
Figure 2.7	Collision of highway users into the temporary signing area (January - November 2023)	26
Figure 2.8	Relation between types of collision, when the collision occurred and injuries suffered by PLUS workers	27
Figure 2.9	Standing at the back of a moving lorry while the back door is open is a violation under Malaysia Road Transportation Department	31
Figure 2.10	The Auto Cone machine installed on a 4x2 chassis vehicle	34
Figure 2.11	The X-Cone 2.0 machine	36
Figure 2.12	The X-Cone 2.0 machine dropping the cone during the cone laying procedure	38
Figure 2.13	The Dynamic Lift System (DLS) by J-Tech	39
Figure 2.14	The X-Cone 2.0 machine dropping the cone during the cone collecting procedure, where (a) the roller panel scoops the cone from the pavement when the lorry is in reverse and (b) the cones are uploaded onto the lorry using the lift	40
Figure 2.15	The Cone Laying and Collecting (C2L) machine	43

FIGURE	TITLE	PAGE
Figure 2.16	Test bed installed at the back of a lorry, where the C2L machine will be hooked onto the sliding rods	44
Figure 2.17	(a) Front and (b) Back view of the C2L body	45
Figure 2.18	The smaller ramp on the left is used when handling the smaller safety cones, while the bigger ramp on the right is used when handling super cones	46
Figure 2.19	Condition of the cone when being held by the ramp	47
Figure 2.20	The AC Motor	48
Figure 2.21	Part of the motion sensors and mechanical sensors installed on the C2L machine	50
Figure 2.22	Roller bearing	51
Figure 2.23	Control panel of the C2L machine	51
Figure 2.24	Control box of the C2L machine	52
Figure 2.25	The Programmable Logic Control (PLC)	53
Figure 2.26	Miniature Circuit Breaker (MCB)	54
Figure 2.27	The Fuse	55
Figure 2.28	The condition of the C2L machine when the guide post is (a) folded (not in use) and (b) unfolded (ready to be used	56
Figure 2.29	The breakdown of each component of the guide post.	57
Figure 2.30	The worker loading a cone onto the ramp during cone laying procedure	59
Figure 2.31	The tipping bar pushes the cone up into the correct position	60
Figure 2.32	Lorry moving in reverse during cone collecting procedure	62
Figure 2.33	The ramp scoops the cones from the pavement	63
Figure 2.34	Removing cone from the ramp	63
Figure 2.35	The relation between MTTF, MTBF and MTTR with operation time, downtime and repair time	70

FIGURE	TITLE	PAGE
Figure 2.36	TRIZ General Problem Solution	78
Figure 2.37	The Function Model (FM) of the C2L Machine	80
Figure 2.38	Cause and Effect Chain Analysis (CECA) diagram	81
Figure 3.1	The Cone Laying and Collecting (C2L) machine	96
Figure 3.2	Research flow chart	98
Figure 3.3	The Cone Laying and Collecting (C2L) machine setup on the test rig and the length of the test rig is 3.13 meters	101
Figure 3.4	The control panel of the test rig	103
Figure 3.5	The motor of the test rig	104
Figure 3.6	The sensors on the test rig	105
Figure 3.7	The chains that move the C2L machine across the test rig	106
Figure 3.8	The rails of the test rig	106
Figure 3.9	(a) The design of the humps (b) The condition of humps, indicated by red arrow, installed in the rail	107
Figure 3.10	Interaction between bearing and C2L body	115
Figure 3.11	Interaction between chains and bearing case	116
Figure 3.12	Interaction between cone and cone lifter	117
Figure 3.13	Movement of cone lifter when collecting cone	119
Figure 3.14	(a) Connecting the movement between gear and chain during cone collecting procedure and (b) Movement of cone lifter during cone collecting procedure	119
Figure 3.15	Movement of cone lifter when laying cone	120
Figure 3.16	Connecting movement between gear, chain and cone lifter during cone laying procedure	121
Figure 3.17	Components within C2L machine that will receive strain during operation: a) Chain and Sprocket, (b) Bearing, (c) Gear, (d) Spring, (e) Motor and (f) Structure	122

FIGURE	TITLE	PAGE
Figure 3.18	A graphical representation of a Function Model (FM)	127
Figure 3.19	Interactions between components and product within a system and supersystem	128
Figure 3.20	Basic Substance-Field Model, where S1 and S2 are Substance and F is the Field	131
Figure 3.21	Incomplete model of the Su-Field analysis	132
Figure 3.22	Ineffective model of the Su-Field analysis	132
Figure 3.23	Harmful model of the Su-Field analysis	133
Figure 3.24	Measurement model of the Su-Field analysis	133
Figure 3.25	(Left) Safety cone and (Right) Super cone	135
Figure 3.26	The setup of Field Test using The C2L machine version 02	136
Figure 3.27	Orientation of the cones during Field Test	138
Figure 3.28	Orientation of the Super Cones and Safety Cones during Field Test 2	139
Figure 4.1	(a) Roller that is used control the vertical movement of the ramp and (b) The location of the roller in the ramp	147
Figure 4.2	(a) Crack on the welded joint, below the ramp and (b) Condition of the joint after rewelding	148
Figure 4.3	The location of the chains that was dislodged from the gear is shown in the red circle	149
Figure 4.4	The lock that holds the guidepost dislodges from position	150
Figure 4.5	Faulty sensor at the right side of C2L machine	151
Figure 4.6	(a) The broken hook spring, which connects the chain to the cone lifter and (b) Condition of the hook spring after replacement	156
Figure 4.7	Boxplot between Test Motion A and Test Motion B on the Total distance travelled on test rig per minute (m/min)	162
Figure 4.8	Boxplot between Test Motion A and Test Motion B on the Total actual distance travelled per minute (m/min)	166

FIGURE	TITLE	PAGE
Figure 4.9	Boxplot between Test Motion A and Test Motion B on the Total laying and collecting movements per minute (count/min)	169
Figure 4.10	Condition of the cone being held by the ramp, which is supported by the welded joint	185
Figure 4.11	Interaction between components that handles the cone	186
Figure 4.12	Su-Field model between Cone and Ramp	186
Figure 4.13	Su-Field model showing the improved interaction between Cone and Ramp	187
Figure 4.14	Interaction between PLC and other components	188
Figure 4.15	Su-Field model between C2L body and PLC	189
Figure 4.16	Su-Field model showing the improved interaction between C2L body and PLC	190
Figure 4.17	Hook spring functions as connector between the chain and the load, which is part of the cone lifter	190
Figure 4.18	Interaction between hook spring, load and cone	191
Figure 4.19	Su-Field model between Load and Hook Spring	191
Figure 4.20	Su-Field of the improved interaction between Spring hook and Load	193
Figure 4.21	(a) Old design of Ramp with straight bar and (b) New design of Ramp with triangular bar, (c) Condition of PLC without damper and (d) Condition of PLC with damper, (e) Using hook spring to hold the load and (f) Using spring hook to hold the load	194
Figure 4.22	(a) Old design of C2L, before redesigning parts that failed during Lab test and (b) New C2L design (C2L 02)	195

LIST OF ABBREVIATIONS

<i>AiCl</i>	-	Advanced Academia Industry Collaboration Laboratory
<i>AC</i>	-	Alternating Design
<i>AD</i>	-	Axiomatic Design
<i>BKE</i>	-	Butterworth-Kulim Expressway
<i>C2L</i>	-	Cone Collecting and Laying
<i>CECA</i>	-	Cause and Effect Chain Analysis
<i>CFD</i>	-	Computational Fluid Dynamics
<i>CCR</i>	-	Cutter Changing Robot
<i>DC</i>	-	Direct Current
<i>DLS</i>	-	The Dynamic Lift System
<i>ELITE</i>	-	Expressway Lingkaran Tengah Sdn. Bhd
<i>FM</i>	-	Function Model
<i>FTME</i>	-	Faculty of Technology and Mechanical Engineering
<i>IFR</i>	-	Ideal Final Result
<i>Linkedua</i>	-	Linkedua (Malaysia) Berhad
<i>LBP</i>	-	Low Back Pain
<i>MCB</i>	-	Miniature Circuit Breaker
<i>MHA</i>	-	Malaysian Highway Authority
<i>MTBF</i>	-	Mean Time Before Failure
<i>MTTF</i>	-	Mean Time to Failure
<i>MTTR</i>	-	Mean Time to Repair
<i>NKVE</i>	-	New Klang Valley Expressway
<i>NRF</i>	-	Non-repairable Failures

<i>NSECL</i>	-	The North-South Expressway Central Link
<i>PBSM</i>	-	Penang Bridge Sdn Bhd
<i>PEB</i>	-	PLUS Expressways Berhad
<i>PMB</i>	-	PLUS Malaysia Berhad
<i>PLC</i>	-	Programmable Logic Control
<i>PLUS</i>	-	Projek Lebuhraya Usahasama Berhad
<i>PLUS Berhad</i>	-	Projek Lebuhraya Utara-Selatan Berhad
<i>QFD</i>	-	Quality Function Deployment
<i>RAMD</i>	-	Reliability, Availability, Maintainability, and Dependability
<i>RF</i>	-	Repairable Failures
<i>SPDH</i>	-	Seremban-Port Dickson Highway
<i>SRB</i>	-	Spherical roller bearings
<i>TRIZ</i>	-	The Theory of Inventive Problem Solving
<i>USSR</i>	-	Union of Soviet Socialist Republics
<i>UTeM</i>	-	Universiti Teknikal Malaysia Melaka
<i>WMDs</i>	-	Work-related musculoskeletal disorder

UNIVERSITI TEKNIKAL MALAYSIA MELAKA


LIST OF SYMBOLS

F	-	Force
k	-	Spring constant
x	-	Change in length



LIST OF APPENDICES

APPENDIX	TITLE	PAGE
Appendix A	Temporary Signing Procedure Involving Emergency Lanes and Slow Lane	238
Appendix B	The Dimension, Weight, Colour, Material And Design Of Super Cones	239
Appendix C	The Dimension, Weight, Colour, Material And Design Of Safety Cones	238
Appendix D	The Design of the Rails of the Test Rig	239
Appendix E	Sub-Class List Of The 76 Standard Inventive Solutions	238
Appendix F	Procedure Of Installing C2l Machin At A Lorry To Execute Cone Laying And Collecting Procedure	239



LIST OF PUBLICATIONS

The followings are the list of publications related to the work on this thesis:

M. Reza, M. A. Salim, N. A. Masripan, N. M. Yusof and M. R. A. Prunomo, 2023. Improving the efficiency of operating the Cone Laying and Collecting Machine (C2L) using TRIZ Method. *Journal of Advanced Manufacturing Technology*, vol. 17, no.3, 2023.



CHAPTER 1

INTRODUCTION

1.1 Background

PLUS Malaysia Berhad (PMB) was originally founded as Highway Concessionaires Berhad on June 1986 before changing its name to Projek Lebuhraya Utara Selatan Berhad on May 1988. PMB was incorporated on November 2010 (PLUS, 2023). A year after that, Projek Lebuhraya Usahasama Berhad (PLUS) was born. As of 2023, the PLUS highway is still the largest toll expressway operator in Malaysia. It consist of the North-South Expressway (NSE), New Klang Valley Expressway (NKVE), Seremban-Port Dickson Highway (SPDH), North-South Expressway Central Link (NSECL), Linkedua, Butterworth-Kulim Expressway (BKE) and the Penang Bridge, which stretches to approximately 945km.

Projek Lebuhraya Usahasama Berhad (PLUS) was established on 2011 following the incorporation of PLUS Malaysia Berhad (PMB) a year before (PLUS, 2023). Currently, PLUS is the biggest toll highway operator in Malaysia, managing several highways including the North-South Expressway (NSE) and New Klang Valley Expressway (NKVE), which covers a total distance of about 946.5km.

The daily traffic volume along PLUS highway is approximately 1.5 million vehicles. Hence, proper maintenance and repair work are constantly conducted so that the highway assets are maintained to the highest standard. This will ensure that the highway users can experience a smooth and safe driving along their journey.

Everytime a maintenance or repair work needs to be done, it needs to be preceded with the temporary signing procedure. The temporary signing procedure refers to the action of closing several affected lanes. Proper signages and cones are set up on areas leading to and around the location where maintenance work will be done. By doing so, incoming traffic will be alerted about the work done on the roads ahead. The drivers can then carefully steer their vehicles into the lanes that are not closed, maintaining the fluidity of the traffic movement along the highway.

When a driver reaches closer to the area where the temporary signing procedure is being executed, the first area that the driver will see is the Advance Warning Zone. There will be a series of signages arranged within the zone to provide early warning to incoming vehicles of the lane closure ahead. After the driver passes the Advance Warning Zone, the driver will reach the Transition Zone. By aranging several super cones and arrows in a tapered orientation, the drivers are guided to move into open lanes. The Buffer Zone comes next to the Transition Zone, which is an area that provides a safety buffer area for both workers and driver. This area is free from equipments and vehicles, but safety cones are used to enclose this area. The most impotart area is the Work Zone, which is the area where the maintenance work and repair work happens. The length of the Work Zone depends on the type of the work that needs to be conducted. Safety cones are arranged parallel along the zones to separate the work area with live traffic. The bright coloured cones would also alert the drivers to be careful when driving along the Work Zone. The Termination Zone is at the end, also enclosed by safety cones and a signboard, which is a small area that helps traffic to merge back into the normal traffic lanes.